

DS320S Bar

320W deep-red-weighted supplemental bar

Specifications

POWER	320 W
PPF	896 $\mu\text{mol/s}$
COVERAGE	Flower 2ft x 4ft; Veg 4ft x 5ft
INPUT VOLTAGE	120-277VAC / 277-480VAC, 50/60Hz (rated input 110-277V)
DIMMING	0-100% dimmer knob
DIMENSIONS	36"L x 4.33"W x 5.04"H (915 x 110 x 128 mm)
WEIGHT	4.8 kg
RATED LIFETIME	50,000 h
WARRANTY	5 years standard



Key features

- 896 $\mu\text{mol/s}$, 320W at 277VAC.
- Deep-red-weighted full spectrum: a defined blue peak near 450nm, a broad 500-620nm base and a dominant peak near 660nm.
- 2ft x 4ft flowering, 4ft x 5ft vegetative coverage, 120° beam.
- Truss-frame construction, 36" x 4.33" x 5.04", 4.8kg, with the driver externally mounted for heat separation.
- Two hanging bails for fast positioning between rows or over a gutter.
- 0-100% dimmer knob; 120-277VAC or 277-480VAC input, power factor above 0.95.
- Passive cooling to 40°C ambient, mounting height 6-24 inches.
- Five-year standard warranty, L90 beyond 50,000 hours.